Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application. Please amend claims 5-7, 22-23, 28-29, 46-48, 57 and 62, as follows:

Listing of claims:

1. (Original) An image processing circuit, comprising: a pixel circuit operable to,

compare a pixel value to a threshold value, and modify the pixel value if the pixel value has a predetermined relationship to the threshold value.

- 2. (Original) The image processing circuit of claim 1 wherein the pixel value comprises a luminance pixel value.
- 3. (Original) The image processing circuit of claim 1 wherein the pixel value comprises a chrominance pixel value.
- 4. (Original) The image processing circuit of claim 1 wherein the threshold value is within a range of approximately 50 80.
- 5. (Currently Amended) The image processing circuit of claim [1] <u>10</u> wherein the compensation value comprises a randomly generated value.
- 6. (Currently Amended) The image processing circuit of claim [1] 10 wherein the compensation value comprises a randomly generated value within a range of [–3 3] (-3) to (+3).
- 7. (Currently Amended) The image processing circuit of claim [1] 10 wherein the pixel circuit is further operable to:

determine whether the sum of the pixel and compensation values value is within a predetermined range of pixel values; and

A1, could

set the <u>pixel value sum</u> equal to a value within the range if the sum is outside of the range.

- 8. (Original) The image processing circuit of claim 1 wherein the pixel circuit is operable to modify the pixel value if the pixel value is less than the threshold value.
- 9. (Original) The image processing circuit of claim 1 wherein the pixel circuit comprises a processor.
- 10. (Original) The image processing circuit of claim 1 wherein the pixel circuit is operable to modify the pixel value by adding a compensation value to the pixel value.
 - 11. (Original) An image processing circuit, comprising: a pixel circuit operable to,

generate a random number, and combine the random number with a pixel value.

- 12. (Original) The image processing circuit of claim 11 wherein the pixel circuit is further operable to truncate the random number before combining the random number with the pixel value.
- 13. (Original) The image processing circuit of claim 11 wherein the pixel circuit is further operable to clip the pixel value if the pixel value is outside of a predetermined range.
- 14. (Original) The image processing circuit of claim 11 wherein the pixel circuit is operable to add the random number to the pixel value.
 - 15. (Original) An image processing circuit, comprising: a pixel circuit operable to,

compare a first pixel value to a first threshold value, the first pixel value corresponding to a pixel location in a first video frame,

add a first compensation value to the first pixel value if the first pixel value is less than the first threshold value,

compare a second pixel value to a second threshold value, the second pixel value corresponding to the pixel location in a second video frame, and

add a second compensation value to the second pixel value if the second pixel value is less than the second threshold value.

- 16. (Original) The image processing circuit of claim 15 wherein the first and second pixel values comprise respective luminance pixel values.
- 17. (Original) The image processing circuit of claim 15 wherein the first and second pixel values comprises respective chrominance pixel values.
- 18. (Original) The image processing circuit of claim 15 wherein the first and second threshold values are within a range of approximately 50 80.
- 19. (Original) The image processing circuit of claim 15 wherein the first threshold value equals the second threshold value.
- 20. (Original) The image processing circuit of claim 15 wherein the first and second compensation values comprise respective randomly generated numbers.
- 21. (Original) The image processing circuit of claim 15 wherein the first compensation value equals the second compensation value.
- 22. (Currently Amended) The image processing circuit of claim 15 wherein the first and second compensation values comprise respective randomly generated numbers within a range of [-3 3] (-3) to (+3).
- 23. (Currently Amended) The image processing circuit of claim 15 wherein the pixel circuit is further operable to:

compare determine if a [the] first sum of the first pixel and first compensation values is less than zero;

and the <u>determine if a</u> second sum of the second pixel and second compensation values [to] <u>is less than</u> zero; and

set the first <u>pixel value sum</u> equal to zero if the first sum is less than zero and set the second <u>pixel value sum</u> equal to zero if the second sum is less than zero.

24. (Original) An image processing circuit, comprising:

a pixel circuit operable to,

generate a first random number using a first seed number,

compare a first pixel value to a first threshold value,

add the first random number to the first pixel value if the first pixel value is less than the first threshold value,

generate a second random number using a second seed number,
compare a second pixel value to a second threshold value, and
add the second random number to the second pixel value if the second pixel
value is less than the second threshold value.

25. (Original) The image processing circuit of claim 24 wherein the pixel circuit is operable to:

truncate the first random number before adding the first random number to the first pixel value; and

truncate the second random number before adding the second random number to the second pixel value.

- 26. (Original) The image processing circuit of claim 24 wherein the second seed number equals the first random number.
- 27. (Original) The image processing circuit of claim 24 wherein the second seed number equals the first seed number.
- 28. (Currently Amended) [The] An image processing circuit, comprising of claim 24 wherein the pixel circuit is operable to:

a pixel circuit operable to,

generate a first random number using a first seed number,

genera

compare a first pixel value to a first threshold value,

add the first random number to the first pixel value if the first pixel value is less than the first threshold value,

truncate the first random number before adding the first random number to the first pixel value;

generate a second random number using a second seed number,

compare a second pixel value to a second threshold value,

add the second random number to the second pixel value if the second pixel

value is less than the second threshold value,

truncate the second random number before adding the second random number to the second pixel value; <u>and</u>

set the second seed number equal to the untruncated first random number.

29. (Currently Amended) [The] <u>An</u> image processing circuit, <u>comprising</u>: of claim 24

a pixel circuit operable to,

generate a first random number using a first seed number,

compare a first pixel value to a first threshold value,

add the first random number to the first pixel value if the first pixel value is less than the first threshold value,

generate a second random number using a second seed number,

compare a second pixel value to a second threshold value, and

add the second random number to the second pixel value if the second pixel value is less than the second threshold value, wherein the pixel circuit is operable to generate the first and second random numbers using the following equation:

 $random\ number = (1664525\ x\ seed\ number + 1013904223) mod\ 2^{32}.$

A² d

- 30. (Original) The image processing circuit of claim 24 wherein: the first pixel value corresponds to a first pixel location in an image; and the second pixel value corresponds to a second pixel location in the image, the second pixel location contiguous with the first pixel location.
- 31. (Original) An image processing circuit, comprising:
 a pixel circuit operable to,
 generate a first random number using a first seed number,
 compare a first pixel value to a first threshold value, the first pixel value
 corresponding to a starting pixel location in a first video frame

add the first random number to the first pixel value if the first pixel value is less than the first threshold value,

generate a second random number using a second seed number,
compare a second pixel value to a second threshold value, the second pixel
value corresponding to a starting pixel location in a second video frame, and
add the second random number to the second pixel value if the second pixel
value is less than the second threshold value.

- 32. (Original) The image processing circuit of claim 31 wherein the second seed number equals the first seed number.
- 33. (Original) The image processing circuit of claim 31 wherein the pixel circuit is further operable to:

generate a third random number using a third seed number;

compare a third pixel value to a third threshold value, the third pixel value corresponding to an ending pixel location in the first video frame;

add the third random number to the third pixel value if the third pixel value is less than the third threshold value; and

set the second seed number equal to the third random number.

361 1116

34. (Original) An image processing circuit, comprising: a pixel circuit operable to, generate a first random number, add the first random number to a first pixel value, generate a second random number, and add the second random number to a second pixel value.

- 35. (Original) The image processing circuit of claim 34 wherein the pixel circuit is operable to generate the first and second random numbers from respective first and second seed numbers.
- 36. (Original) The image processing circuit of claim 34 wherein the pixel circuit is operable to:

generate the first random number from a seed number; and generate the second random number from the first random number.

37. (Original) The image processing circuit of claim 34 wherein: the first pixel value corresponds to a pixel location in a first video frame; the second pixel value corresponds to the pixel location in a second video frame; and

the first random number equals the second random number.

38. (Original) The image processing circuit of claim 34 wherein:
the first pixel value corresponds to a starting pixel location in a first video frame;
the second pixel value corresponds to the pixel location in a second video frame;
and

the first random number does not equal the second random number.

39. (Original) A circuit, comprising:

a comparator having a pixel-value input terminal and first and second pixel-value output terminals;

a random-number generator having a seed input terminal and a random-number output terminal;

a combiner having a first input terminal coupled to the first pixel-value output terminal, a second input terminal coupled to the random-number output terminal, and a combiner output terminal; and

an image buffer having a first input terminal coupled to the second pixel-value output terminal and having a second input terminal coupled to the combiner output terminal.

- 40. (Original) The circuit of claim 39 wherein the comparator is operable to receive a pixel value on the pixel-value input terminal, provide the pixel value on the first pixel-value output terminal if the pixel value is less than a threshold value, and provide the pixel value on the second pixel-value output terminal if the pixel value is greater than the threshold value.
- 41. (Original) The circuit of claim 39 wherein the random-number output terminal is coupled to the seed input terminal.
- 42. (Original) The circuit of claim 39 wherein the combiner comprises a summer.
- 43. (Original) The circuit of claim 39, further comprising a random-number truncator disposed between the random-number generator and the combiner, the truncator having an input terminal coupled to the random-number output terminal of the random-number generator and having an output terminal coupled to the second input terminal of the combiner.
- 44. (Original) The circuit of claim 39, further comprising a clipper disposed between the combiner and the image buffer, the clipper having an input terminal coupled to the combiner output terminal and having an output terminal coupled to the second input terminal of the image buffer.

- 45. (Original) A method, comprising:
 comparing a pixel value to a threshold value; and
 modifying the pixel value if the pixel value has a predetermined relationship to
 the threshold value.
 - 46. (Currently Amended) The method of claim [45] <u>50</u>, further comprising: generating a random number; and setting the compensation value equal to the random number.
 - 47. (Currently Amended) The method of claim [45] <u>50</u>, further comprising: generating a random number; truncating the random number to a number within a range of [–3 3] <u>(-3) to (+3)</u>;

setting the compensation value equal to the truncated random number.

48. (Currently Amended) The method of claim [45] <u>50</u>, further comprising: determining whether the sum of the pixel and compensation <u>values</u> is within a predetermined range of pixel values; and

setting the <u>pixel-value</u> <u>sum</u> equal to a value within the range if the sum is outside of the range.

- 49. (Original) The method of claim 45 wherein the modifying comprises modifying the pixel value if the pixel value is less than the threshold value.
- 50. (Original) The method of claim 45 wherein the modifying comprises adding a compensation value to the pixel value.
 - 51. (Original) A method, comprising:generating a random number; andcombining the random number with a pixel value.

and

- 52. (Original) The method of claim 51, further comprising truncating the random number before combining the random number with the pixel value.
- 53. (Original) The method of claim 51, further comprising clipping the pixel value if the pixel value is outside of a predetermined range.
 - 54. (Original) A method, comprising:

comparing a first pixel value to a first threshold value, the first pixel value corresponding to a pixel location in a first video frame;

adding a first compensation value to the first pixel value if the first pixel value is less than the first threshold value;

comparing a second pixel value to a second threshold value, the second pixel value corresponding to the pixel location in a second video frame; and

adding a second compensation value to the second pixel value if the second pixel value is less than the second threshold value.

- 55. (Original) The method of claim 54 wherein the first threshold value equals the second threshold value.
- 56. (Original) The method of claim 54 wherein the first and second compensation values equal the same randomly generated number.
- 57. (Currently Amended) The method of claim 54, further comprising: comparing determining if a first sum of the first pixel and first compensation values [to] is less than zero;

setting the first <u>sum</u> <u>pixel value</u> equal to zero if the first sum is less zero; comparing <u>determining if</u> a second sum of the second pixel and second compensation values [to] <u>is less than</u> zero; and

setting the second <u>sum pixel value</u> equal to zero if the second sum is less than zero.

A2'd

58. (Original) A method, comprising:

generating a first random number using a first seed number; comparing a first pixel value to a first threshold value;

adding the first random number to the first pixel value if the first pixel value is less than the first threshold value;

generating a second random number using a second seed number;
comparing a second pixel value to a second threshold value; and
adding the second random number to the second pixel value if the second pixel
value is less than the second threshold value.

59. (Original) The method of claim 58 wherein:

the generating the first random number comprises truncating the first random number; and

the generating the second random number comprises truncating the second random number.

- 60. (Original) The method of claim 58 wherein the second seed number equals the first random number.
- 61. (Original) The method of claim 58 wherein the second seed number equals the first seed number.
 - 62. (Currently Amended) [The] A method, comprising:of claim 58 generating a first random number using a first seed number; comparing a first pixel value to a first threshold value;

adding the first random number to the first pixel value if the first pixel value is less than the first threshold value;

generating a second random number using a second seed number; comparing a second pixel value to a second threshold value; and

adding the second random number to the second pixel value if the second pixel value is less than the second threshold value, wherein the generating the first and second random numbers comprises generating the first and second random numbers are generated according to the following equation:

 $random\ number = (1664525\ x\ seed\ number + 1013904223) mod\ 2^{32}$.

63. (Original) A method, comprising: generating a first random number using a first seed number; comparing a first pixel value to a first threshold value, the first pixel value

corresponding to a starting pixel location in a first video frame;

adding the first random number to the first pixel value if the first pixel value is less than the first threshold value;

generating a second random number using a second seed number;
comparing a second pixel value to a second threshold value, the second pixel
value corresponding to a starting pixel location in a second video frame; and
adding the second random number to the second pixel value if the second pixel
value is less than the second threshold value.

- 64. (Original) The method of claim 63, further comprising setting the second seed number equal to the first seed number.
- 65. (Original) The method of claim 63, further comprising:
 generating a third random number using a third seed number;
 comparing a third pixel value to a third threshold value, the third pixel value
 corresponding to an ending pixel location in the first video frame;

adding the third random number to the third pixel value if the third pixel value is less than the third threshold value; and

setting the second seed number equal to the third random number.

66. (Original) A method, comprising: generating a first random number;

Azid

adding the first random number to a first pixel value; generating a second random number; and adding the second random number to a second pixel value.

- 67. (Original) The method of claim 66 wherein the generating the first and second random numbers comprises generating the first and second random numbers from respective first and second seed numbers.
 - 68. (Original) The method of claim 66 wherein:

the generating the first random number comprises generating the first random number from a seed number; and

the generating the second random number comprises generating the second random number from the first random number.

69. (Original) The method of claim 66 wherein:
the first pixel value corresponds to a pixel location in a first video frame;
the second pixel value corresponds to the pixel location in a second video frame;
and

the generating the second random number comprises generating the second random equal to the first random number.

70. (Original) The method of claim 66 wherein: the first pixel value corresponds to a starting pixel location in a first video frame; the second pixel value corresponds to the pixel location in a second video frame; and

the generating the second random number comprises generating the second random number unequal to the first random number.

A2 could